

License Plate Camera



SPECS



About 200g



-40°C ~+70°C



196.7 x 29.5 x 30 mm



0% to 95%

Product overview

The license plate camera is specially designed to be installed on the license plate, with strong performance of the image quality and processing, IP69K rated for dust, pressure and water protection.

Product features

- **Compact rear license plate mount**
- **Waterproof with IR for night visibility**
- **Ideal for reverse monitoring**
- **Integrates with MDVR or InsightHub**

vestigeview.com

PRODUCT SPECIFICATIONS

Model	CA38 (A6620LS)
Image sensor	1/2.9" 2.0Mp progressive scan CMOS
Effective Pixels	1920(H) x 1080(V)
Video signal standards	NTSC/PAL
Minimum illumination	0.05Lux (color), 0Lux (IR on)
Shutter speed	1/25s-1/25,000s (auto)
Day-to-night mode	ICR
Adjustment angle	Up (horizontally): 30°; down (horizontally): 45°
Backlight compensation	Supported
S/N	≥48db
DWDR	Supported
White balance	Auto tracking of white balance
Auto gain	Supported
3D noise reduction	Supported
IR range	3-5m
Lens	2.2mm M12 lens (DFOV:178°; HFOV: 142°; VFOV: 80°)
Video output	1.0Vp-p composite video output, 75Ω, 4Pin aviation cable
Power supply	DC12V± 10%
Power consumption (max)	130mA/DC12V±5% (max 1.6W)
Dimensions	196.7 x 29.5 x 30 mm (L x W x H)
Net weight	About 200g
Operating temperature	-40°C ~ 70°C
Operating humidity	0% - 90%
IP rating	IP69K
Installation mode	Supported to be installed on the rear license plate



vestigeview.com


vestigeTM
Your Safety is OUR Priority