

Mini Dome Camera



SPECS

• About 168g

• 69mm x 55.5mm

• -40°C ~+70°C

Product overview

The Mini Dome Camera features a durable metal housing designed for rugged and vandal-prone environments. Vibration and thermal tested, it's ideal for mobile applications. Equipped with a CMOS sensor, it delivers excellent image quality in all lighting conditions and includes an integrated microphone for clear audio capture.

Product features

- 1.3M pixel CMOS
- 2.5\2.8\3.6MM optional
- Easy to assemble and install; lockable angle and anti-vibration design
- Perfect solutions for vehicle monitoring, bus, coach, tipper, van, road sweeper, fuel tanker

SPECIFICATION

Model	SVT6220H(AHD 1080P)	SVT-6210H(AHD 720P)	SVT-M5270H(CVBS 800TVL)
CMOS	1/2.9" 2M pixel CMOS	1/3" 1.3M pixel CMOS	1/3" 1.3M pixel CMOS
Resolution	1920H x 1080V	1280H x 720V	800 TVL
Format	NTSC/PAL		
Minimum illumination	0.1Lux(IR off) /0Lux (IR on) F1.2		
IR distance	3 ~ 5m	5 ~ 8m	5 ~ 8m
S/N	≥ 45dB	≥ 52dB	≥ 52dB
Lens	2.8,3.6mm M12(Optional)	2.5,2.8,3.6mm M12(Optional)	2.5,2.8,3.6mm M12(Optional)
FOV	NC	2.5mm H x V 105 x 61°	2.5mm H x V 105 x 61°
	2.8mm H x V 90 x 47°	2.8mm H x V 88 x 50°	2.8mm H x V 88 x 50°
	3.6mm H x V 81 x 42°	3.6mm H x V 72 x 41°	3.6mm H x V 72 x 41°
Video output	1.0Vp-p AHD video output 75 Ω, 4pin DIN JACK	1.0Vp-p AHD video output, 75 Ω, 4pin DIN JACK	1.0Vp-p Composite video output, 75 Ω, 4pin DIN JACK
Audio		Built-in mic	
Power		DC12V± 10%	
Power consumption (max)		120mA/DC12V ±5%	
Operating temperature		-40°C ~ 70°C	
Dimensions		69(W) x 55.5(H)mm	
Net weight		About 168g	



vestigeview.com

vestigeTM
Your Safety is OUR Priority