

Road Condition Camera



SPECS

-  150g
-  85 x 54.5 x 39 mm
-  -40°C ~+70°C
-  < 90% (non-condensing)

Product features

- 1/3" 1.3M pixel CMOS
- Resolution: 1280H*720V
- Minimum illumination: 0.01Lux (color)
- Auto electronic shutter, auto exposure and auto white balance
- Support stepless angle adjustment
- Compact and aesthetic appearance makes easy installation possible

vestigeview.com

PRODUCT SPECIFICATIONS

Model	SVT-A6410MS
Image sensor	1/3" 1.3M pixel CMOS
Resolution	1280H*720V
Video signal standards	NTSC/PAL
Minimum illumination	0.01lux (color)
Electronic shutter	1/25s-1/25,000s (auto)
Synchronization system	Internal synchronization
Scanning system	Progressive scan
S/N	≥ 50dB
Lens	2.4mm M12@F2.0lens; HFOV: 112° VFOV: 86°
White balance	Auto tracking of white balance
Day-to-night	Full color mode (no IR)
Auto gain	Supported
Backlight compensation	Supported
3D noise reduction	Supported
Gamma correction	0.45
WDR	50DB
Video output	AHD coaxial HD standard, 4Pin aviation cable
Power supply	DC12V± 10%
Power consumption (max)	70mA±10mA
Operating temperature	-40°C ~ 70°C
Operating humidity	<90% (non-condensing)
Dimensions	85mm x 54.5mm x 39mm (L x W x H)
Net weight	About 150g



vestigeview.com